



SEALON®

JOINT SEALANT

SEALON® JOINT SEALANT

INSTALLATION

SEALON JOINT SEALANT has high tensile strength and flexible and tough properties, it has no drawback as seen in existing gaskets. Playing a sealing role firmly, easily and economically even under extremely severe corrosive conditions, SEALON JOINT SEALANT is an almighty gasket packing, oval in cross section and string shape, with superior chemical and heat resistance.

Installation

SEALON JOINT SEALANT is a soft, pliable, flexible PTFE having an adhesive back for ease of installation on vertical surfaces.



1. Clean flange, removing scale and other foreign materials.
2. Strip off the Release paper, push the adhesion surface at the center of flange surface, and stick on there in a ring shape.
3. Edge of it is overlapped 1 to 2cm at the bolt seat.
4. Fix the flange to the opponent and tighten each bolts uniformly, then it is flattened ribbon-like to 1.5 times width and the over lapped part is closely in contact.

SEALON®

JOINT SEALANT

SEALON® is a registered trademark of YMT



YEU MING TAI CHEMICAL INDUSTRIAL CO., LTD.

P.O. BOX 46-196, TAICHUNG INDUSTRIAL PARK, TAICHUNG, TAIWAN (407)

<http://www.ymt.com.tw>

MADE IN TAIWAN